

LEDspan Siaph LED Light Luminaire

Model No: LSLL



Siaph



- ▶ LED Luminaire fitting for modular ceilings.
- ▶ LEDspan Saiph has an overall efficiency of 150lm/w.
- ▶ 2mm aluminum IMS PCB is durable and a heat sink.
- ▶ Available in three versions 62W, 84W, and 108W .
- ▶ >55% energy saving than T5 and >71% energy saving over T8.
- ▶ LEDspan underdrive technology for reduced heat and increased lifetime.
- ▶ 62W replaces 4x36W T8, 84w replaces 4x54WT8.
- ▶ Sensor & Dali versions available.

Electrical Characteristics

LED Source:	Everlight
Input voltage:	220-240V AC
Wattage:	62W, 84W or 108W
Power Factor:	>0.95
Lumen o/p 62/82/108W	7440, 10,800, 12800
Lumen Deprecation:	>1% at 6,000 hours @ 55C
CCT:	4000k(3 step MacAdam)
CRI:	>82ra
Lifetime:	>70,000 hours to L70
Working Temp:	-20°C to +60°C

“Leaders in Energy
Efficient Cleanroom
Lighting Excellence”

Features

- LEDspans 'Siaph' High Efficiency LED Luminaire designed to replace modular fluorescent fixtures in cleanroom and other controlled / industrial environments.
- High Output LEDs allow high lux levels using existing fitting locations.
- Intergral 6W independent emergency circuit gives >600 lumens of light in emergency mode.
- DALI dimmable versions available for increased control and further energy reduction.



LEDspan operates a continuous improvement policy and reserves the right to change specification at any time.

www.LEDspan.com